

HIGHLIGHTS	
TOUGH	 Heavy-duty Rotax® engine Smooth, durable and responsive transmission True Can-Am DNA with a strong identity
CAPABLE	Work or ride with confidence Meaningful and versatile functionality Easy handling and capabilities
CLEVER	 Advanced comfort and intuitive cockpit with optimized visibility Multifunction cargo box with sturdy tailgate and smart storage 1 year maintenance-free and easy access to key maintenance components
PLATFORM FEATURES	• 62 in. wide • 83 in. wheelbase • 11 in. of ground clearance • 2,500 lb towing capacity • Multifunction cargo box • 14 in. steel wheels with 27 in. XPS Trail Force tires • Rear differential with Turf mode • VERSA-PRO bench seat • HMWPE central skid plate • ECO™/ECO™ Off/Workmodes • 4.5 in. wide digital display

ENGINES	HD7	HD9
Туре	52 hp / 41 lb-ft, Rotax® ACE (Advanced Combustion Efficiency) 650 cc single cylinder, liquid-cooled	65hp/59lb-ft,Rotax°976cc, V-twin,liquid-cooled
Fuel Delivery System	Intelligent Thrott with Electronic F	
Transmission	PDrive primary CVT with engine braking and Electronic Drive Belt Protection L/H/N/R/P	PRO-TORQ CVT Transmission with Quick Response System (QRS), high-airflow ventilation and Electronic Drive Belt Protection
		Extra L/H/N/R/P
Drive Train		rf Mode/2WD/4WD ocking front differential
Driving Assistance	Electronic Hill Descent Control ECO™/ECO™ Off/Work modes	
PowerSteering	N	Ά
SUSPENSIONS FrontSuspension		in. (25.4 cm) travel
Front Shocks	Twin tube gas-charged shocks	
RearSuspension	TTA with external sway bar/10 in. (25.4 cm) travel	
Rear Shocks	Twin tube gas-charged shocks	
TIRES & WHEELS		
Front Tires	XPSTrailForce27x9x14in.	
RearTires	XPSTrailForce27x11x14in.	
Wheels	14 in. steel	
BRAKES		
Front	Dual 220 m	m disc brakes
	with hydraulic tw	in-piston calipers
Rear		m disc brakes gle-piston calipers



CAPACITIES	HD7	HD9	
Chassis/Cage	Profiled cage, ROPS approved		
Estimated Dry Weight	1,475lb(669.2kg)	1,479 lb (671 kg)	
LxWxH	121 x 62 x 76 in. (30	121 x 62 x 76 in. (307.1 x 157.5 x 193 cm)	
Wheelbase	83 in. (21	1.5 cm)	
Ground Clearance	11 in. (2	28cm)	
Cargo Box Dimensions	38 x 54.5 x 12 in. (9	6.5 x 138.4 x 30.5 cm)	
Cargo Box Capacity	1,000 lb (454 kg)/		
	California only:	California only: 600 lb (272.2 kg)	
Power Tilt Bed	N/A		
Tailgate Load Capacity	250 lb (11	250 lb (113.4 kg)	
Storage Capacity	Total: 3.1 gal (11.7 L)		
	Under dash (enclosed p Dash: 1.8		
	Armrests and cup ho		
TowingCapacity	2,500 lb (1,134 kg)	
Payload Capacity	1,500 lb (680 kg)		
Fuel Capacity	10.6 gal (40 L)		
Person Capacity	3		
FEATURES			
Gauge	4.5 in. widedig	jitaldisplay:	
	speedometer, tachometer, odom gear position, ECO™/ECO™ Off/\		

FEATURES	
Gauge	4.5 in. wide digital display: speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, ECO™Df/Work modes, seat belt and 4x4
	indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature
Battery	12 V (18amp/h)
Magneto	650 W
Instrumentation	Lighter-type DC outlet in console (20 A)
Lighting	140 W lighting output from four 35 W reflectors ensuring wide visibility and LED tail lights
Winch	N/A
Seat	VERSA-PRO bench seat with passenger seats flipping up, underside hooks and contoured bench to improve entrance/exit of the cab
Steering Wheel	Adjustable tiltsteering
Protection	Integrated front steel bumper,
	HMWPE central skid plate
Hitch Type	2 in. hitch receiver

/ARRANTY	& EXTENDED	SERVICE

Factory Warranty	1 year BRP limited warranty	
Extended Service Terms	B.E.S.T. term available up to 30 months	





HIGHLIGHTS	HD9	HD10	
TOUGH	Heavy-duty Rotax® engine Smooth, durable and responsive transmission True Can-Am DNA with a strong identity		
CAPABLE	Work or ride with confidence Meaningful and versatile functi Easy handling and capabilities	Meaningful and versatile functionality	
CLEVER	Advanced comfort and intuitive cockpit with optimized visibility Multifunction cargo box with sturdy tailgate and smart storage 1 year maintenance-free and easy access to key maintenance components		
PLATFORM FEATURES	63.5 in. wide 115.5 in. wheelbase 11 in. of ground clearance 2,500 lb towing capacity Multifunction cargo box 27 in. XPS Trail Force Rear differential with Turf mode VERSA-PRO bench seats HMWPE central skid plate 4.5 in. digital display	115.5 in. wheelbase 12.5 in. of ground clearance 2,500 lb towing capacity Multifunction cargo box 27 in. Maxxis Bighorn 2.0 Rear differential with Turf mode VERSA-PRO bench seats HMWPE central skid plate 4.5 in. digital display	
SPECIFIC TO MAX DPS PACKAGE	Dynamic Power Steering (DPS) Visco-Lok QE front differential 14 in. cast-aluminum wheels Mossy Oak® Break-Up Country Camo water-dipped option	64 in. wide with Arched A-arm Dynamic Power Steering (DPS) Visco-Lok QE front differential 14 in. cast-aluminum wheels	
		•	

ENGINE	HD9	HD10
Туре	65 hp / 59 lb-ft , Rotax® 976 cc, V-twin, liquid-cooled	82 hp/69 lb-ft, Rotax® 976 cc, V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	
Transmission	PRO-TORQ CVT Transmission with Quick Response System (QRS) high-airflow ventilation and Electronic Drive Belt Protection Extra L/H/N/R/P	
Drive Train	Selectable Turf Mode / 2WD/4WD with Visco-Lok† QE auto-locking front differential	
Driving Assistance	Electronic Hill Descent Control ECO™/ECO™ Off/Work modes	
Power Steering	Dynamic Power Steering (DPS)	
SUSPENSIONS		
Front Suspension	Double A-arm/10 in. (25.4 cm) travel	Arched double A-arm/11 in. (27.9 cm) travel
Front Shocks	Twin tube gas-charged shocks	
Rear Suspension	TTA with external sway bar/ 10 in. (25.4 cm) travel	Arched TTA with external sway bar/11 in. (27.9 cm) travel
Rear Shocks	Twin tube gas-charged shocks	
TIRES & WHEELS		
Front Tires	XPS Trail Force 27 x 9 x 14 in.	Maxxis Bighorn 2.0 27 x 9 x 14 in.
Rear Tires	XPS Trail Force 27 x 11 x 14 in.	Maxxis Bighorn 2.0 27 x 11 x 14 in.
Wheels	14 in. cast-aluminum	
BRAKES		
Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers	
Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers	



CAPACITIES	HD9	HD10
Estimated Dry Weight	1,771 lb (803.2 kg)	1,771.2 lb (803.4 kg)
LxWxH	153.4 x 63.5 x 76 in. (389.6 x 161.2 x x 193 cm)	153.4 x 64 x 77.5 in. (389.6 x 162.5 x x 196.9 cm)
Wheelbase	115.5 in.	(294 cm)
Ground Clearance	11 in. (28 cm)	12.5 in. (31.8 cm)
Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)	
Cargo Box Capacity	1,000 lb (454 kg)/California only: 600 lb (272.2 kg)	
Power Tilt Bed	N/A	
Tailgate Load Capacity	250 lb (113.4 kg)	
Storage Capacity	Total: 11.1 gal (42.1 L) Under dash: 6 gal (22.8 L) Dash: 1.8 gal (6.9 L) Water-resistant and removable toolbox: 1.7 gal (6.3 L) Armrests and cup holders: 1.6 gal (6.1 L)	
Towing Capacity	2,500 lb (1,134 kg)	
Payload Capacity	1,750 lb (793,8 kg)	
Fuel Capacity	10.6 gal (40 L)	
Person Capacity		6

FEATURES	
Gauge	4.5 in. wide digital display: speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, ECO™/ECO™ Off/Work modes, seat belt, diagnostics, clock, battery voltage, engine temperature
Battery	12 V (18 amp/h)
Magneto	650 W
Instrumentation	Lighter-type DC outlet in console (20 A)
Lighting	140 W lighting output from four 35 W reflectors ensuring a wide visiblity and LED tail lights
Winch	N/A
Seat	Dual VERSA-PRO bench seats with passenger seats flipping up, underside hooks and contoured bench to improve entrance/exit of the cab
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper, HMWPE central skid plate
Hitch Type	2 in. hitch receiver

WARRANTY & EXTENDED SERVICE	
Factory Warranty	1 year BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months





HIGHLIGHTS

TOUGH	Heavy-duty Rotax* engine Smooth, durable and responsive transmission True Can-Am DNA with a strong identity
CAPABLE	Work or ride with confidence Meaningful and versatile functionality Easy handling and capabilities
CLEVER	Advanced comfort and intuitive cockpit with optimized visibility Multifunction cargo box with sturdy tailgate and smart storage 1 year maintenance-free and easy access to key maintenance components
PLATFORM FEATURES	• 83 in. wheelbase • 12 in. of ground clearance • Dynamic Power Steering (DPS) • ECO™/ECO™ Off/Work modes • 2,500 lb towing capacity • Multifunction cargo box • 27 in. XPS Trail Force tires • Rear differential with Turf mode
SPECIFIC TO Limited PACKAGE	65 in. wide with Arched A-arm LED Signature Visco-Lok front differential 14 in. cast-aluminum wheels VERSA-PRO bolster bench seat with reinforced Limited seat skin and adjustable driver seat HMWPE full skid plate 4,500 lb (2,014 kg) winch XT front bumper Full hard roof with liner and interior dome light Full color-match doors with electric opening windows 3-position full glass tilt up windshield with wiper/washer kit Rear glass window Full hard roof with liner and interior dome light Auto heating and air conditioning (HVAC) climate system

|--|

Type	82 hp/69 lb-ft, Rotax 976 cc, V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PRO-TORQ CVT Transmission with Quick Response System (QRS), high-airflow ventilation and Electronic Drive Belt Protection Extra L/H/N/R/P
Drive Train	Selectable Turf Mode/2WD/4WD with Visco-Lok¹ auto-locking front differential
Driving Assistance	Electronic Hill Descent Control ECO™/ECO™ Off/Work modes
Power Steering	Dynamic Power Steering (DPS)

Brake holding mechanismPanoramic mirror

• Mossy Oak® Break-Up Country Camo water-dipped option

SUSPENSIONS

ENGINE

Front Suspension	Arched double A-arm with sway bar/10 in. (25.4 cm) travel
Front Shocks	Twin tube gas-charged shocks
Rear Suspension	Arched TTA with external sway bar/10 in. (25.4 cm) travel
Rear Shocks	Twin tube gas-charged shocks

TIRES & WHEELS

Front Tires	XPS Trail Force 27 x 9 x 14 in.
Rear Tires	XPS Trail Force 27 x 11 x 14 in.
Wheels	14 in. cast-aluminum

BRAKES

Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm disc brakes with hydraulic single-piston calipers
	Brake-holding mechanism



Stone Gray / HD10 Oxford Blue / HD10

Mossy Oak® Break-Up Country Camo / HD10

DIMENSIONS & CAPACITIES

CAFACITIES	
Chassis/Cage	Profiled cage, ROPS approved
Estimated Dry Weight	1,928 lb (874.5 kg)
LxWxH	126 x 65 x 79 in. (319 x 165.1 x 201 cm)
Wheelbase	83 in. (211.5 cm)
Ground Clearance	12 in. (30.5 cm)
Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)
Cargo Box Capacity	1,000 lb (454 kg)/California only: 600 lb (272.2 kg)
Power Tilt Bed	N/A
Tailgate Load Capacity	250 lb (113.4 kg)
Storage Capacity	Total: 12.7 gal (48.1 L) Waterproof and removable box under passenger seat: 5.6 gal (21 L) Dash: 2 gal (7.7 L) Water-resistant and removable toolbox: 1.7 gal (6.3 L) Under dash: 1.6 gal (6.1 L) Armrests and cup holders: 0.9 gal (3.5 L) Interior doors: 0.8 gal (3.4 L)
Towing Capacity	2,500 lb (1,134 kg)
Payload Capacity	1,200 lb (544 kg)
Fuel Capacity	10.6 gal (40 L)
Person Capacity	

Gauge	7.6 in. wide digital display with keypad:
· ·	speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, ECO TM /ECO TM Off/Work modes, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature
Battery	12 V (30 amp/h)
Magneto	850 W
Instrumentation	Lighter-type DC outlets in the console (10 A) and two lighted USB ports in the dash storage (10 A)
Lighting	140 W lighting output from four 35 W reflectors ensuring wide visibility, signature LED and LED tail lights
Winch	4,500 lb (2,041 kg) winch with roller fairlead
Seat	VERSA-PRO bolster bench seats for additional lateral support with passenger seats flipping up, adjustable driver seat, underside hooks, reinforced seat skin featuring Limited package trims and contoured bench to improve entrance/exit of the cab
Steering Wheel	Adjustable tilt steering
Protection	XT front bumper, HMWPE full skid plate, full hard roof with liner and interior dome light, full color-match doors with electric opening windows, 3-position full glass tilt-up windshield with wiper/washer kit, rear glass window
Hitch Type	2 in. hitch receiver

Factory Warranty	1 year BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



Can-am. COMMANDER DPS 1000R

HIGHLIGHTS

PERFORMANCE	Proven Rotax engine Dependable drivetrain Sport segment-worthy suspension
WORKABILITY	Rugged taskmaster Work-oriented functionality Vehicle protection and rigidity
DESIGN & ERGONOMICS	Interior focused on comfort Superior fit and finish Low cost of ownership
PLATFORM FEATURES	90.6 in. wheelbase 12.5 in. ground clearance Up to 13 in. of suspension travel 2,000 lb towing capacity Dynamic Power Steering (DPS™) Visco-Lok¹ QE front differential SPORT/ECO™ modes D.E.S.S. key with Start/Stop button 4.5 in. digital display Premium half door Mudguard Rear differential with Turf mode

ENGINE	1000R
Туре	100 hp, Rotax® 976 cc, V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high-airflow ventilation and Electronic Drive Belt Protection Extra-L/H/N/R/P
Drive Train	Selectable Turf Mode/2WD/4WD with Visco-Lok† QE auto-locking front differential
Driving Assistance	Electronic Hill Descent Control SPORT/ECO™ modes
Power Steering	Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Double A-arm with sway bar/12.5 in. (31.8 cm) travel
Front Shocks	Twin-tube gas-charged shocks
Rear Suspension	TTA with sway bar/13 in. (33 cm) travel
Rear Shocks	Twin-tube gas-charged shocks

TIRES & WHEELS

Front Tires	XPS Trail Force 27 x 9 x 14 in.
Rear Tires	XPS Trail Force 27 x 11 x 14 in.
Wheels	14 in. steel

BRAKES

Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers



Tundra Green / 1000R

DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,600 lb (725.5 kg)
Chassis/Cage	Profiled cage. ROPS approved
LxWxH	128.5 x 62 x 70.5 in. (326.3 x 157.5 x 180.2 cm)
Wheelbase	90.6 in. (230.1 cm)
Ground Clearance	12.5 in. (31.8 cm)
Cargo Box Dimensions	29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)
Cargo Box Capacity	600 lb (272.2 kg)
Towing Capacity	2,000 lb (907.2 kg)
Payload Capacity	1,030 lb (467.2 kg)
Storage Capacity	Total: 7.3 gal (27.6 L) Glove box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and cup holders: 0.8 gal (3.1 L) Side cargo box storage (passenger side): 1.6 gal (5.9 L) Dual side panel storage: 0.8 gal (3.0 L)
Fuel Capacity	10 gal (38 L)

FEATURES

Gauge	4.5 in. wide digital display: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature
Instrumentation	Lighter-type DC outlet in console (10 A)
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Magneto	650 W
Lighting	Two 55 W reflector headlights (low/high) and LED tail lights
Winch	N/A
Steering Wheel	Adjustable tilt steering
Protection	Premium half doors
	Full skid plate
	Mudguards
Hitch Type	2 in. hitch receiver

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



COMMANDER MAX XT 1000R

HIGHLIGHTS

PERFORMANCE	Proven Rotax engine Dependable drivetrain Sport segment-worthy suspension
WORKABILITY	Rugged taskmaster Work-oriented functionality Vehicle protection and rigidity
DESIGN & ERGONOMICS	Interior focused on comfort Superior fit and finish Low cost of ownership
PLATFORM FEATURES	120.6 in. wheelbase 13 in. ground clearance 15 in. suspension travel 2,000 lb towing capacity Dynamic Power Steering (DPS™) Visco-Lok¹ QE front differential SPORT/ECO™ modes D.E.S.S. key with Start/Stop button Premium half doors Mudguards Rear differential with Turf mode
SPECIFIC TO XT PACKAGE	64 in. wide with arched double A-arm 28 in. XPS Trail King tires 14 in. cast-aluminum wheels XT front bumper Full roof 4,500 lb (2,014 kg) winch 7.6 in. digital display with keypad Can-Am LED signature

ENGINE	1000R

Туре	100 hp, Rotax® 976 cc, V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with-high airflow ventilation and Electronic Drive Belt Protection Extra-L/H/N/R/P
Drive Train	Selectable Turf Mode/2WD/4WD with Visco-Lok† QE auto-locking front differential
Driving Assistance	Electronic Hill Descent Control SPORT/ECO™ modes
Power Steering	Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Arched double A-arm with sway bar/15 in. (38.1 cm) travel
Front Shocks	Twin-tube gas-charged shocks
Rear Suspension	Arched TTA with sway bar/15 in. (38.1 cm) travel
Rear Shocks	Twin-tube gas-charged shocks

TIRES & WHEELS

Front Tires	XPS Trail King 28 x 9 x 14 in.
Rear Tires	XPS Trail King 28 x 11 x 14 in.
Wheels	14 in. cast-aluminum

BRAKES

Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers



DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,930 lb (875.4 kg)
Chassis/Cage	Profiled cage ROPS approved
LxWxH	160.4 x 64 x 76.2 in. (407.3 x 162.6 x 193.5 cm)
Wheelbase	120.6 in. (306.3 cm)
Ground Clearance	13 in. (33 cm)
Cargo Box Dimensions	29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)
Cargo Box Capacity	600 lb (272.2 kg)
Towing Capacity	2,000 lb (907.2 kg)
Payload Capacity	1,280 lb (580.6 kg)
Storage Capacity	Total: 8.5 gal (32.1 L) Glove box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and cup holders: 0.8 gal (3.1 L) Rear console and cup holders: 1.2 gal (4.5 L) Side cargo box storage (passenger side): 1.6 gal (5.9 L) Dual side panel storage: 0.8 gal (3.0 L)
Fuel Capacity	10 gal (38 L)

FEATURES

Gauge	7.6 in. wide digital display with keypad: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO TM modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature
Instrumentation	Lighter-type DC outlet in console (10 A)
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Magneto	650 W
Lighting	Two 55 W reflectors headlights with unique Can-Am LED signature and LED tail lights
Winch	4,500 lb (2,041 kg) winch with roller fairlead
Steering Wheel	Adjustable tilt steering
Protection	Premium half doors Full skid plate Mudguards Full roof XT front bumper
Hitch Type	2 in. hitch receiver

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



COMMANDER MAX XT-P 1000R

HIGHLIGHTS

PERFORMANCE	 Proven Rotax engine Dependable drivetrain Sport segment-worthy suspension
WORKABILITY	 Rugged taskmaster Work-oriented functionality Vehicle protection and rigidity
DESIGN & ERGONOMICS	 Interior focused on comfort Superior fit and finish Low cost of ownership
PLATFORM FEATURES	120.6 in. wheelbase 13 in. ground clearance 15 in. suspension travel 2,000 lb towing capacity Dynamic Power Steering (DPS™) Visco-Lok¹ QE front differential SPORT/ECO™ modes D.E.S.S. key with Start/Stop button Premium half doors Mudguards Rear differential with Turf mode
SPECIFIC TO XT-P PACKAGE	64 in. wide with arched double A-arm Smart-Lok* front differential FOX' 2.5 PODIUM QS3 Piggyback shocks 30 in. XPS Hammer Force tires 15 in. cast-aluminum beadlock wheels XT front bumper 4,500 lb (2,014 kg) winch Full roof and panoramic mirror 7.6 in. digital display with keypad LED headlight and Can-Am LED signature Painted-color and special-edition seats

ENGINE	1000R	
Туре	100 hp, Rotax® 976 cc, V-twin, liquid-cooled	
Fuel Delivery System	Intelligent Throttle Control (iTC™)	

Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	
Transmission	Quick Response System (QRS) CVT with high-airflow ventilation and Electronic Drive Belt Protection Extra-L/H/N/R/P	
Drive Train	Selectable Turf Mode / 2WD/4WD TRAIL / 4WD TRAIL ACTIV with exclusive Smart-Lok *technology.	
Driving Assistance	Electronic Hill Descent Control SPORT/ECO™ modes	
Power Steering	Dynamic Power Steering (DPS)	

SUSPENSIONS

Front Suspension	Arched double A-arm with sway bar/14 in. (35.6 cm) travel	
Front Shocks	FOX† 2.5 PODIUM Piggyback with QS3† compression adjustment	
Rear Suspension	Arched TTA with sway bar/14 in. (35.6 cm) travel	
Rear Shocks	FOX [†] 2.5 PODIUM Piggyback with QS3 [†] compression adjustment	

TIRES & WHEELS

Front Tires	XPS Hammer Force 30 x 10 x 15 in.	
Rear Tires	XPS Hammer Force 30 x 10 x 15 in.	
Wheels	15 in. cast-aluminum beadlock	

BRAKES

DITTULE	
Front Dual 220 mm disc brakes with hydraulic twin-pistor	
Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers



DIMENSIONS & CAPACITIES

Estimated Dry Weight	2,000 lb (907.2 kg)
Chassis/Cage	Profiled cage ROPS approved
LxWxH	160.4 x 64 x 76.7 in. (407.3 x 162.6 x 194.8 cm)
Wheelbase	120.6 in. (306.3 cm)
Ground Clearance	13.5 in. (34.3 cm)
Cargo Box Dimensions	29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)
Cargo Box Capacity	600 lb (272.2 kg)
Towing Capacity	2,000 lb (907.2 kg)
Payload Capacity	1,280 lb (580.6 kg)
Storage Capacity	Total: 8.5 gal (32.1 L) Glove box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and cup holders: 0.8 gal (3.1 L) Rear console and cup holders: 1.2 gal (4.5 L) Side cargo box storage (passenger side): 1.6 gal (5.9 L) Dual side panel storage: 0.8 gal (3.0 L)
Fuel Capacity	10 gal (38 L)

FEATURES

Gauge	7.6 in. wide digital display with keypad: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO TM modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature
Instrumentation	Lighter-type DC outlet in console (10 A)
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Magneto	650 W
Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	4,500 lb (2,041 kg) winch with roller fairlead
Steering Wheel	Adjustable tilt steering
Protection	Premium half doors Full skid plate Mudguards XT front bumper Full roof
Hitch Type	2 in. hitch receiver

Factory Warranty	6-month BRP limited warranty	
Extended Service Terms	B.E.S.T. term available up to 30 months	



CON-OTT. MAVERICK SPORT MAX DPS 1000R

HIGHLIGHTS

manifiant	
DARING	 Sturdy engine and transmission Enhanced comfort and meaningful functionalities Can-Am design
PRECISE	Easy handling and capabilitiesSuspension designed for performanceUltra-resistant chassis
CONFIDENT	Perfectly tuned Enhanced protection More adventure and less maintenance
PLATFORM FEATURES	• 60 in. wide • 120.6 in. wheelbase • 12 in. of ground clearance • Up to 13 in. of suspension travel • SPORT/ECO™ modes • 4.5 in. digital display • Premium half door • Mudguard
SPECIFIC TO DPS PACKAGE	Dynamic Power Steering (DPS™) Visco-Lok¹ QE front differential Ergoprint seats with color accents



Triple Black / 1000R

ENGINE	1000R

Туре	100 hp, Rotax® 976 cc, V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high-airflow ventilation and Electronic Drive Belt Protection Extra-L/H/N/R/P
Drive Train	Selectable 2WD/4WD with Visco-Lok QE auto-locking front differential
Driving Assistance	Electronic Hill Descent Control SPORT/ECO™ modes
Power Steering	Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Double A-arm with sway bar/11.5 in. (29.2 cm) travel
Front Shocks	SHOWA 2.0
Rear Suspension	TTA with sway bar/12 in. (30.5 cm) travel
Rear Shocks	SHOWA 2.0

TIRES & WHEELS

Front Tires	Maxxis Bighorn 2.0 27 x 9 x 12 in.
Rear Tires	Maxxis Bighorn 2.0 27 x 11 x 12 in.
Wheels	12 in. cast-aluminum
BRAKES	
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm ventilated disc brakes

with hydraulic twin-piston calipers

DIMENSIONS & CAPACITIES

CAPACITIES	
Estimated Dry Weight	1,697 lb (769.7 kg)
Chassis/Cage	Profiled cage, ROPS approved
LxWxH	149 x 60 x76.2 in. (378.4 x 152.4 x 193.5 cm)
Wheelbase	120.6 in. (306.3 cm)
Ground Clearance	12 in. (30.5 cm)
Cargo Box Capacity	300 lb (136 kg)
Towing Capacity	1,500 lb (680 kg)
Storage Capacity	Total: 6.5 gal (24.7 L) Glove box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and cup holders: 0.8 gal (3.1 L) Rear console and cup holders: 1.2 gal (4.5L)
Fuel Capacity	10 gal (38 L)
FEATURES	
Gauge	4.5 in, wide digital display:

Gauge	speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ modes, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature
Instrumentation	Lighter type DC outlet in console (20 A)
Magneto	650 W
Lighting	Two 55 W reflectors and LED tail lights
Winch	N/A
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper, Premium half doors, Full skid plate, Mudguards
Hitch Type	2 in. hitch receiver

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



CON-OM. MAVERICK SPORT X rc 1000R

HIGHLIGHTS

HIGHLIGHIS	
DARING	Sturdy engine and transmission Enhanced comfort and meaningful functionalities Can-Am design
PRECISE	Easy handling and capabilitiesSuspension designed for performanceUltra-resistant chassis
CONFIDENT	Perfectly tuned Inhanced protection More adventure and less maintenance
PLATFORM FEATURES	• 90.6 in. Wheelbase • 15 in. of ground clearance • 14.75 in. suspension travel • Dynamic Power Steering (DPS™) • SPORT/ECO™ modes • Premium half door • Mudguard
SPECIFIC TO X rc PACKAGE	64 in. wide with arched A-arm Smart-Lok* front differential FOX† 2.5 PODIUM† QS3 piggyback shocks 30 in. Maxxis† Liberty† tires

 FOX[†] 2.5 PODIUM[†] QS3 piggy
 30 in. Maxxis[†] Liberty[†] tires
 14 in. cast-aluminum wheels
 4,500 lb (2,041 kg) winch with
 Rear sport bumper, front anch

Front

Rear

4,500 lb (2,041 kg) winch with synthetic cable
Rear sport bumper, front anchor
HMWPE front skid plate and rock sliders
UHMWPE front and rear suspension arm protectors

X-package graphics/seats
 7.6 in. digital display with keypad

Can-Am LED signature and premium tail light

ENGINE	1000R
Туре	100 hp, Rotax® 976 cc, V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high-airflow ventilation and Electronic Drive Belt Protection Extra-L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok technology True 4-mode traction system: 2WD/4WD with front differential lock/4WD ROCK/4WD TRAIL
Driving Assistance	Electronic Hill Descent Control SPORT/ECO™ modes
Power Steering	Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Arched double A-arm with sway bar/14.8 in. (37.6 cm) travel
Front Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment
Rear Suspension	Arched TTA with sway bar/14.8 in. (37.6 cm) travel
Rear Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment
TIRES & WHEELS	
Front Tires	Maxxis Liberty 30 x 10 x 14 in.
Rear Tires	Maxxis Liberty 30 x 10 x 14 in.
Wheels	14 in. cast-aluminum
BRAKES	



1,593 lb (722.6 kg)

Chalk Gray & Magma Red / 1000R

DIMENSIONS & CAPACITIES

Factory Warranty

Extended Service Terms

Estimated Dry Weight

LStilliated Dry Weight	1,595 ib (722.0 kg)
Chassis/Cage	Profiled cage, ROPS approved
L×W×H	122 x 64 x 74.25 in. (309.8 x 162.6 x 188.6 cm)
Wheelbase	90.6 in. (230.1 cm)
Ground Clearance	15 in. (38.1 cm)
Cargo Box Capacity	300 lb (136 kg)
Towing Capacity	1,500 lb (680 kg)
Storage Capacity	Total: 5.3 gal (20.2 L) Glove box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and cup holders: 0.8 gal (3.1 L)
Fuel Capacity	10 gal (38 L)
FEATURES	
Gauge	7.6 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ modes, seat bel and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature
Instrumentation	Lighter type DC outlet in console (20 A)
Magneto	650 W
Lighting	Two 55 W reflectors with unique Can-Am LED signature and LED tail lights with halo glow effect
Winch	4,500 lb (2,041 kg) winch with synthetic rope
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper, Rear sport bumper, Premium half doors, Mudguards, Front tow hook Full skid plate, UHMWPE rock sliders, Panoramic mirror HMWPE skid plates: Differential and front skid plate/front and rear suspension arm
Hitch Type	2 in, hitch receiver



6-month BRP limited warranty

B.E.S.T. term available up to 30 months

Dual 220 mm ventilated disc brakes

with hydraulic twin-piston calipers

Dual 220 mm ventilated disc brakes

with hydraulic twin-piston calipers

Can-am. MAVERICK X3 DS TURBO

HIGHLIGHTS

DEFIANT	Trademark Can-Am DNA with next generation design Low seating position Ergo-Lok cockpit with four-way adjustable seats
POWERFUL	120 hp turbocharged Rotax® ACE engine Advanced airflow dynamics QRS-X transmission
PRECISE	TTX suspension with industry-leading travel Ultra efficient and lightweight chassis Sharpest handling features
PLATFORM FEATURES	• 64 in. wide • 102 in. wheelbase • 14 in. of ground clearance • High-torque Dynamic Power Steering (DPS™) • 20 in. suspension travel • FOX 2.5 PODIUM QS3 piggyback shocks • 14 in. aluminum wheels • 30 in. Maxxis Carnivore tires • 4.5 in. digital display with keypad • Rear tow hook



ENGINE	TURBO
Туре	120 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled and high-perfomance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok* technology. True 4-mode traction system: 2WD/4WD with front diff. lock/4WD TRAIL ACTIV/4WD TRAIL
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Double A-arm with sway bar/20 in. (50.8 cm) travel
Front Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar/20 in. (50.8 cm) travel
Rear Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment and bottom-out control
TIRES & WHEELS	
Front Tires	Maxxis Carnivore 30 x 10 x 14 in.
Rear Tires	Maxxis Carnivore 30 x 10 x 14 in.
Wheels	14 in. cast-aluminum
BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers

DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,546 lb (701.3 kg)
Chassis/Cage	Dual-phase 980 steel
LxWxH	132 x 64 x 65.4 in. (335.3 x 162.5 x 166.1 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	14 in. (35.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)
Fuel Capacity	10.5 gal (40 L)

FEATURES	
Gauge	4.5 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode
Instrumentation	Lighter-type DC outlet in central console
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlights and tail lights
Winch	N/A
Magneto	650 W
Protection	Integrated front bumper Quarter doors HMWPE full skid plate Rear tow hook

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



can-am. MAVERICK X3 X mr TURBO RR 72"

HIGHLIGHTS

DEFIANT	 Trademark Can-Am DNA with next-generation design Low seating position Ergo-Lok cockpit with four-way adjustable seats
POWERFUL	Industry-leading 200 hp turbocharged and intercooled Rotax* ACE engine Advanced airflow dynamics QRS-X transmission
PRECISE	TTX suspension with industry-leading travel Ultra efficient and lightweight chassis Sharpest handling features
PLATFORM FEATURES	 •72 in. wide •102 in. wheelbase •16 in. of ground clearance •High-torque Dynamic Power Steering (DPS™) •22 in. suspension travel •FOX 2.5 PODIUM QS3 piggyback shocks •Rear tow hook
SPECIFIC TO X mr TURBO RR 72" PACKAGE	Belt-monitoring system 200 hp Turbo RR engine Smart-Lok [™] front differential Snorkeled engine air intake and CVT 14 in. aluminum beadlock wheels 30 in. ITP Cryptid tires Front bumper, half-doors Front tow hook HMWPE full skid plate 4,500 lb (2,041kg) winch with synthetic rope X-package graphics/seats 7.6 in. digital display with keypad Can-Am LED signature 850 W magneto Painted color

ENGINE	TURBO RR
Туре	200 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler, high-perfomance air filter and strategically positioned engine air intake
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary and Quick Response System X (QRS-X) CVT, high airflow with strategically positioned CVT air intake and exhaust, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 4-mode traction system: 2WD/4WD with front diff. lock/4WD MUD/4WD TRAIL
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Arched double A-arm with sway bar/22 in. (55.9 cm) travel/Trophy truck-inspired arms
Front Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustmen
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links/22 in. (55.9 cm) travel
Rear Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment and bottom-out control
TIRES & WHEELS	
Front Tires	ITP Cryptid 30 x 9 x 14 in.
Rear Tires	ITP Cryptid 30 x 11 x 14 in.
Wheels	14 in. cast-aluminum beadlock
BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes



1,758 lb (797.4 kg)

Dual-phase 980 steel

Liquid Titanium & Magma Red / TURBO RR

DIMENSIONS & CAPACITIES

Chassis/Cage

Estimated Dry Weight

LxWxH	132.3 x 74.2 x 68 in. (336 x 188.5 x 172.7 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	16 in. (40.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)
Fuel Capacity	10.5 gal (40 L)
FEATURES	
Gauge	7.6 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode
Instrumentation	Lighter-type DC outlet in central console
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	4,500 lb (2,041 kg) winch with synthetic rope
Magneto	850 W
Protection	Front bumper Half doors Front and rear tow hooks HMWPE full skid plate Rear tow hook

WARRANTY &

6-month BRP limited warranty
B.E.S.T. term available up to 30 months



with hydraulic twin-piston calipers

CON-ON. MAVERICK X3 X rs TURBO RR WITH SMART-SHOX

HIGHLIGHTS

ENGINE

півпівпів	
DEFIANT	Trademark Can-Am DNA with next-generation design Low seating position Ergo-Lok cockpit with four-way adjustable seats
POWERFUL	Industry-leading 200 hp turbocharged and intercooled Rotax* ACE engine Advanced airflow dynamics QRS-X transmission
PRECISE	TTX suspension with industry-leading travel Ultra efficient and lightweight chassis Sharpest handling features
PLATFORM FEATURES	 72 in. wide 102 in. wheelbase 16 in. of ground clearance High-torque Dynamic Power Steering (DPS™) Up to 24 in. of suspension travel Rear tow hook
SPECIFIC TO X rs TURBO RR PACKAGE with Smart-Shox	Belt-monitoring system 200 hp Turbo RR engine Smart-Lok™* front differential Smart-Shox** Technology featuring DDA Valve FOX 3.0 PODIUM shocks with bypass 14 in. aluminum beadlock wheels 32 in. Maxxis Carnivore tires 4-point harness with shoulder pads HMWPE full skid plate Full roof X-package graphics/seats 7.6 in. digital display with keypad Can-Am LED signature 850 W magneto Painted color options

THERE DE

ENGINE	TURBO RR
Туре	200 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-perfomance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 4-mode traction system: 2WD/4WD with front diff. lock/4WD TRAIL ACTIV/4WD TRAIL
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Double A-arm with sway bar/22 in. (55.9 cm) travel/ Trophy truck-inspired arms
Front Shocks	FOX 2.5 PODIUM piggyback with bypass and Smart-Shox Technology featuring DDA valve (Dynamic Damping Adjustment)
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar/24 in. (61 cm) travel
Rear Shocks	FOX 3.0 PODIUM remote reservoir with bypass and Smart-Shox Technology featuring DDA valve (Dynamic Damping Adjustment)
TIRES & WHEELS	
Front Tires	Maxxis Carnivore 32 x 10 x 14 in.
Rear Tires	Maxxis Carnivore 32 x 10 x 14 in.
Wheels	14 in. cast-aluminum beadlock
BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers



1,699 lb (770.7 kg)

Intense Blue, Carbon Black & Chalk Gray / TURBO RR
Triple Black / TURBO RR
Desert Tan, Carbon Black & Can-Am Red / TURBO RR

DIMENSIONS & CAPACITIES

Estimated Dry Weight

	., (
Chassis/Cage	Dual-phase 980 steel
LxWxH	132 x 72.7 x 68.5 in. (335.3 x 184.7 x 174 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	16 in. (40.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)
Fuel Capacity	10.5 gal (40 L)
FEATURES	
Gauge	7.6 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode, Smart-Shox Suspension Mode
Instrumentation	Lighter-type DC outlet in central console
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	N/A
Magneto	850 W
Protection	Integrated front bumper Quarter doors Full roof 4-point harness with shoulder pads HMWPE full skid plate Rear tow hook



Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months





Can-am. MAVERICK X3 X rc TURBO RR 72"

HIGHLIGHTS

DEFIANT	Tradomark Can Am DNA with novt concretion decima
DEFIANT	Trademark Can-Am DNA with next-generation design Low seating position Ergo-Lok cockpit with four-way adjustable seats
POWERFUL	Industry-leading 200 hp turbocharged and intercooled Rotax* ACE engine Advanced airflow dynamics QRS-X transmission
PRECISE	 TTX suspension with industry-leading travel Ultra efficient and lightweight chassis Sharpest handling features
PLATFORM FEATURES	 72 in. wide 102 in. wheelbase 16 in. of ground clearance High-torque Dynamic Power Steering (DPS™) Up to 24 in. of suspension travel Rear tow hook
SPECIFIC TO X rc TURBO RR 72" PACKAGE	Belt-monitoring system 200 hp Turbo RR engine Smart-Lok [™] front differential FOX 3.0 PODIUM RC2 shocks with bypass 15 in. aluminum beadlock wheels 32 in. Maxxis Liberty tires Front bumper, half-doors, aluminum roof, intrusion bar Front tow hook HMWPE differential and under-bumper skid plates HMWPE front and rear suspension arm UHMWPE rock sliders

4,500 lb (2,041 kg) winch with synthetic rope
 4-point harness with shoulder pads
 X-package graphics/seats
 7.6 in. digital display with keypad
 Can-Am LED signature
 850 W magneto
 Painted color

ENGINE	TURBO RR
Туре	200 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-perfomance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 4-mode traction system: 2WD/4WD with front diff. lock/4WD ROCK/4WD TRAIL
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Trophy truck-inspired arched double A-arm with sway bar/22 in. (55.9 cm) travel
Front Shocks	FOX 2.5 PODIUM RC2 piggyback with bypass, dual speed compression and rebound adjustments
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links/24 in. (61 cm) travel
Rear Shocks	FOX 3.0 PODIUM RC2 remote reservoir with bypass, dual speed compression and rebound adjustments
TIRES & WHEELS	
Front Tires	Maxxis Liberty 32 x 10 x 15 in.
Rear Tires	Maxxis Liberty 32 x 10 x 15 in.
Wheels	15 in. cast-aluminum beadlock
BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes



1 042 lb (026 kg)

Chalk Gray & Magma Red / TURBO RR

DIMENSIONS & CAPACITIES

Estimated Day Waight

Estimated Dry Weight	1,843 lb (836 kg)
Chassis/Cage	Dual-phase 980 steel
LxWxH	134.5 x 72.8 x 68.5 in. (341.6 x 184.9 x 174 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	16 in. (40.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)
Fuel Capacity	10.5 gal (40 L)
FEATURES	
Gauge	7.6 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode
Instrumentation	Lighter-type DC outlet in central console
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	4,500 lb (2,041 kg) winch with synthetic rope
Magneto	850 W
Protection	Front bumper Half doors Aluminum roof Intrusion bar 4-point harness with shoulder pads UHMWPE rock sliders HMWPE skidplates: Full heavy-duty with differential/Under bumper/Front and rear suspension arm Rear tow book

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



with hydraulic twin-piston calipers



Can-am. MAVERICK X3 MAX DS TURBO

HIGHLIGHTS

IIIdiiLidiiio	
DEFIANT	 Trademark Can-Am DNA with next-generation design Low seating position Ergo-Lok cockpit with front and rear four-way adjustable seats
POWERFUL	 120 hp turbocharged Rotax® ACE engine Advanced airflow dynamics QRS-X transmission
PRECISE	TTX suspension with industry-leading travel Ultra efficient and lightweight chassis Sharpest handling features
PLATFORM FEATURES	• 64 in. wide • 135 in. wheelbase • High-torque Dynamic Power Steering (DPS™) • 20 in. suspension travel • FOX 2.5 PODIUM QS3 piggyback shocks • 13 in. of ground clearance • 14 in. aluminum wheels • 30 in. Maxxis Carnivore tires • 4.5 in. digital display with keypad • Rear tow hook



ENGINE	TURBO
Туре	120 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled and high-perfomance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok* technology. True 4-mode traction system: 2WD/4WD with front diff. lock/4WD TRAIL ACTIV/4WD TRAIL
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Double A-arm with sway bar/20 in. (50.8 cm) travel
Front Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar/20 in. (50.8 cm) travel
Rear Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment and bottom-out control
TIRES & WHEELS	
Front Tires	Maxxis Carnivore 30 x 10 x 14 in.
Rear Tires	Maxxis Carnivore 30 x 10 x 14 in.
Wheels	14 in. cast-aluminum
BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers

DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,810 lb (821 kg)
Chassis/Cage	Dual-phase 980 steel
LxWxH	164 x 64 x 65.8 in. (416.6 x 162.5 x 167.1 cm)
Wheelbase	135 in. (342.9 cm)
Ground Clearance	13 in. (33 cm)
Rack Capacity	150 lb (68 kg) with LinQ™ quick-attach
Storage Capacity	Total: 3 gal (11.4 L) Glove box: 1.6 gal (6.2 L) Central console: 1.1 gal (4.1 L) Cup holders: 0.3 gal (1.1 L)
Fuel Capacity	10.5 gal (40 L)
FEATURES	

4.5 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode Lighter-type DC outlet in central console
speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode
Lighter-type DC outlet in central console
RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
LED headlights and tail lights
N/A
650 W
Integrated front bumper Quarter doors HMWPE full skid plate Rear tow hook

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



CON-OM. MAVERICK X3 MAX X ds TURBO RR

HIGHLIGHTS

IIIdiiLidiiio	
DEFIANT	Trademark Can-Am DNA with next-generation design Low seating position Ergo-Lok cockpit with front and rear four-way adjustable seats
POWERFUL	Industry-leading 200 hp turbocharged and intercooled Rotax® ACE engine Advanced airflow dynamics QRS-X transmission
PRECISE	TTX suspension with industry-leading travel Ultra efficient and lightweight chassis Sharpest handling features
PLATFORM FEATURES	 • 64 in. wide • 135 in. wheelbase • 14 in. of ground clearance • High-torque Dynamic Power Steering (DPS™) • 20 in. suspension travel • 30 in. Maxxis Carnivore tires • Rear tow hook
SPECIFIC TO X ds TURBO RR PACKAGE	Belt-monitoring system 200 hp Turbo RR engine Smart-Lok™* front differential FOX 2.5 PODIUM RC2 Piggyback shocks 14 in. aluminum beadlock wheels X-package graphics/seats 7.6 in. digital display with keypad Can-Am LED signature 850 W magneto Painted color options

ENGINE	TURBO RR
Туре	200 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-perfomance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 4-mode traction system: 2WD/4WD with front diff. lock/4WD TRAIL ACTIV/4WD TRAIL
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Double A-arm with sway bar/20 in. (50.8 cm) travel
Front Shocks	FOX 2.5 PODIUM RC2 piggyback with dual speed compression and rebound adjustments
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar/20 in. (50.8 cm) travel
Rear Shocks	FOX 2.5 PODIUM RC2 piggyback with dual speed compression, rebound adjustments and bottom-out control
TIRES & WHEELS	
Front Tires	Maxxis Carnivore 30 x 10 x 14 in.
Rear Tires	Maxxis Carnivore 30 x 10 x 14 in.
Wheels	14 in. cast-aluminum beadlock
BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers



DIMENSIONS &

CAPACITIES	
Estimated Dry Weight	1,838 lb (833.7 kg)
Chassis/Cage	Dual-phase 980 steel
LxWxH	164 x 64 x 66 in. (416.6 x 162.5 x 167.6 cm)
Wheelbase	135 in. (342.9 cm)
Ground Clearance	13 in. (33 cm)
Rack Capacity	150 lb (68 kg) with LinQ™ quick-attach
Storage Capacity	Total: 3 gal (11.4 L) Glove box: 1.6 gal (6.2 L) Central console: 1.1 gal (4.1 L) Cup holders: 0.3 gal (1.1 L)
Fuel Capacity	10.5 gal (40 L)
FEATURES	
Gauge	7.6 in, wide digital display with keypad:

FEATURES	
Gauge	7.6 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode
Instrumentation	Lighter-type DC outlet in central console
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	N/A
Magneto	850 W
Protection	Integrated front bumper Quarter doors HMWPE full skid plate Rear tow hook

WARRANTY &

EXTENDED SERVICE	
Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



Can-am. MAVERICK X3 MAX X rs TURBO RR WITH SMART-SHOX

HIGHLIGHTS

Belt-monitoring system 200 hp Turbo RR engine Smart-Lok™ front differential Smart-Shox** technology featuring DDA valve FOX 3.0 PODIUM shocks with bypass 14 in. aluminum beadlock wheels 32 in. Maxxis Carnivore tires 4-point harness with shoulder pads HMWPE full skid plate Full roof X-package graphics/seats 7.6 in. digital display with keypad Can-Am LED signature 850 W magneto Painted color options			
 72 in. wide 135 in. wheelbase 16 in. of ground clearance High-torque Dynamic Power Steering (DPS™) 22 in. suspension travel Rear tow hook 			
TTX suspension with industry-leading travel Ultra efficient and lightweight chassis Sharpest handling features			
 Industry-leading 200 hp turbocharged and intercooled Rotax* ACE engine Advanced airflow dynamics QRS-X transmission 			
Trademark Can-Am DNA with next-generation design Low seating position Ergo-Lok cockpit with front and rear four-way adjustable seats			

LINGINE	TORBOTA		
Туре	200 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-perfomance air filter		
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)		
Transmission	PDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P		
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 4-mode traction system: 2WD/4WD with front diff. lock/4WD TRAIL ACTIV/4WD TRAIL		
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS)		
SUSPENSIONS			
Front Suspension	Double A-arm with sway bar/22 in. (55.9 cm) travel/ Trophy truck-inspired arms		
Front Shocks	FOX 2.5 PODIUM piggyback with bypass and Smart-Shox Technology featuring DDA valve (Dynamic Damping Adjustment)		
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar/22 in. (55.9 cm) travel		
Rear Shocks	FOX 3.0 PODIUM remote reservoir with bypass and Smart-Shox Technology featuring DDA valve (Dynamic Damping Adjustment)		
TIRES & WHEELS			
Front Tires	Maxxis Carnivore 32 x 10 x 14 in.		
Rear Tires	Maxxis Carnivore 32 x 10 x 14 in.		
Wheels	14 in. cast-aluminum beadlock		
BRAKES			
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers		
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers		



Intense Blue, Carbon Black & Chalk Gray / TURBO RR
Triple Black / TURBO RR
Desert Tan, Carbon Black & Can-Am Red / TURBO RR

DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,942 lb (880.9 kg)	
Chassis/Cage	Dual-phase 980 steel	
LxWxH	165 x 72.7 x 68.5 in. (419.1 x 184.7 x 174 cm)	
Wheelbase	135 in. (342.9 cm)	
Ground Clearance	16 in. (40.6 cm)	
Rack Capacity	150 lb (68 kg) with LinQ™ quick-attach	
Storage Capacity	Total: 3 gal (11.4 L) Glove box: 1.6 gal (6.2 L) Central console: 1.1 gal (4.1 L) Cup holders: 0.3 gal (1.1 L)	
Fuel Capacity	10.5 gal (40 L)	

10.5 gal (40 L)		
7.6 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode, Smart-Shox Suspension Mode		
Lighter-type DC outlet in central console		
RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button		
LED headlights and tail lights with unique Can-Am LED signature		
N/A		
850 W		
Integrated front bumper Quarter-doors Full roof 4-point harness with shoulder pads HMWPE full skid plate Rear tow hook		

WARRANTY &

EXTENDED SERVICE	
Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



